

RR KĀBEL

# PRICE LIST

Ref No. RRKL/LP/LDC-PIIC/11-2/26

w.e.f. 17th November 2026

RR KĀBEL

# INDIA'S NO.1 EXPORTER OF WIRES & CABLES




REACH • RoHS
CE • CPR
COMPLIANT

FREE FROM
245+
HARMFUL
SUBSTANCES

**SAHI CHUNO**

KĀBEL

# INDUSTRIAL CABLES

## FOR EVERY SECTOR DELIVERING CUTTING-EDGE PERFORMANCE



**REACH • RoHS • CE**

**COMPLIANT**

**FLEXIBLE SINGLE CORE CABLE • FLEXIBLE MULTICORE CABLES**

**SHIELDED CABLE • BRAIDED CABLE**

## FR HSF




Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code: 8544)

| Size (Sq.mm) | * Configuration | AMPS | Unit | Rate | No. of Coils packed in an Outer Box |
|---|---|---|---|---|---|
| 0.75 | 24/0.2 | 8 | 200 Mtr | 5868 | 12 |
| 1.0 | 32/0.2 | 13 | 200 Mtr | 7665 | 12 |
| 1.5 | 30/0.25 | 17 | 200 Mtr | 11086 | 8 |
| 2.5 | 50/0.25 | 24 | 200 Mtr | 18046 | 6 |
| 4.0 | **56/0.31** | 30 | 200 Mtr | 27748 | 4 |
| 6.0 | 84/0.3 | 38 | 200 Mtr | 41261 | 2 |

* As per IS 8130

## RR KABEL FR-LSH




Single Core unsheathed Multistrand High Conductivity plain annealed copper, FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code:8544)

| Size (Sq.mm) | * Configuration | AMPS | Unit | Rate | No. of Coils packed in an Outer Box |
|---|---|---|---|---|---|
| 0.75 | 24/0.2 | 8 | 200 Mtr | 5986 | 12 |
| 1.0 | 32/0.2 | 13 | 200 Mtr | 7820 | 12 |
| 1.5 | 30/0.25 | 17 | 200 Mtr | 11308 | 8 |
| 2.5 | 50/0.25 | 24 | 200 Mtr | 18408 | 6 |
| 4.0 | **56/0.31** | 30 | 200 Mtr | 28303 | 4 |
| 6.0 | 84/0.3 | 38 | 200 Mtr | 42086 | 2 |

* As per IS 8130

## LS0H-EBXL




Single Core unsheathed Multistrand High Conductivity plain annealed copper, E-Beam cross-linked Halogen Free Flame retardant (HFFR) Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 17048 (HSN Code:8544)

| Size (Sq.mm) | * Configuration | AMPS | Unit | Rate | No. of Coils packed in an Outer Box |
|---|---|---|---|---|---|
| 0.75 | 24/0.2 | 13 | 200 Mtr | 6738 | 12 |
| 1.0 | 32/0.2 | 21 | 200 Mtr | 8490 | 12 |
| 1.5 | 30/0.25 | 27 | 200 Mtr | 11944 | 8 |
| 2.5 | 50/0.25 | 34 | 200 Mtr | 19333 | 6 |
| 4.0 | **56/0.31** | 46 | 200 Mtr | 29637 | 4 |
| 6.0 | 84/0.3 | 59 | 200 Mtr | 43950 | 2 |

* As per IS 8130

## RR KABEL FR HSF / FR-LSH / LS0H-FR




Single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts ( HSN Code : 8544)

| RATE / 100 MTR | | | | | |
|---|---|---|---|---|---|
| Size (Sq.mm) | ** Configuration | AMPS | RR KABEL FR HSF FR PVC INSULATION As Per IS 694 | RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694 | RR KABEL LSOH-FR Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048 |
| 10.0 | 140/0.3 | 52 | 36486 | 37216 | 40127 |
| 16.0 | 126/0.4 | 70 | 57749 | 58904 | 63196 |
| 25.0 | 196/0.4 | 88 | - | 90808 | 97799 |
| 35.0 | 276/0.4 | 112 | - | 127026 | 136795 |
| 50.0 | 396/0.4 | 146 | - | 181149 | 195081 |
| 70.0 | 360/0.5 | 216 | - | 256722 | 276468 |
| 95.0 | 480/0.5 | 262 | - | 345350 | 371914 |
| 120.0 | 608/0.5 | 310 | - | 446860 | 481233 |
| 150.0 | 750/0.5 | 355 | - | 553941 | 596546 |
| 185.0 | 931/0.5 | 415 | - | 673697 | 725506 |
| 240.0 | 1200/0.5 | 500 | - | 886295 | 954473 |
| 300.0 | 1500/0.5 | 550 | - | 1106458 | 1191569 |
| 400.0 * | 2013/0.5 | 590 | - | 1503526 | 1619175 |
| 500.0 * | 2562/0.5 | 660 | - | 1948920 | 2098836 |
| 630.0 * | 3416/0.5 | 725 | - | 2590682 | 2789970 |

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

* As per IS 8130

## RR KABEL FR HSF SINGLE CORE




Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | * Configuration | AMPS | Rate Per 100 Mtr |
|---|---|---|---|
| 0.5 | 16/0.2 | 5 | 2087 |
| 0.75 | 24/0.2 | 8 | 2935 |
| 1.0 | 32/0.2 | 13 | 3832 |
| 1.5 | 30/0.25 | 17 | 5544 |
| 2.5 | 50/0.25 | 24 | 9024 |
| 4.0 | 56/0.3 | 30 | 13874 |
| 6.0 | 84/0.3 | 38 | 20631 |

* As per IS 8130

KĀBEL

# RATNA FLEX MULTICORE CABLES




Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

| Rate per 100 meter | | | | | |
|---|---|---|---|---|---|
| Size (Sq.mm) | CONFIG. | AMPS | 2 CORE | 3 CORE | 4 CORE |
| 0.5 | 16/0.2 | 5 | 5626 | 7423 | 9400 |
| 0.75 | 24/0.2 | 8 | 7407 | 10050 | 12938 |
| 1.0 | 32/0.2 | 13 | 9121 | 12769 | 16467 |
| 1.5 | 30/0.25 | 17 | 12607 | 17592 | 22900 |
| 2.5 | 50/0.25 | 24 | 20004 | 28216 | 36698 |
| 4.0 | 56/0.3 | 30 | 30949 | 43411 | 56871 |
| 6.0 | 84/0.3 | 38 | 44621 | 63642 | 83742 |
| 10.0 | 140/0.3 | 52 | 79229 | 113530 | 147939 |
| 16.0 | 126/0.4 | 70 | 123785 | 174822 | 230355 |

Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & FR-LSH PVC sheathed multicore round flexible industrial cables for working voltage upto and including 1100 Volts, as per IS 694 (HSN Code : 8544)

| Size (Sq.mm) | CONFIG. | AMPS | 2 CORE | 3 CORE | 4 CORE |
|---|---|---|---|---|---|
| 25.0 | 196/0.4 | 88 | 198779 | 281803 | 371274 |
| 35.0 | 276/0.4 | 112 | - | 393530 | 521487 |
| 50.0 | 396/0.4 | 146 | - | 561757 | 731569 |
| 70.0 | 360/0.5 | 216 | - | 790352 | 1041917 |
| 95.0 | 480/0.5 | 262 | - | 1066163 | 1397971 |
| 120.0 | 608/0.5 | 310 | - | 1345984 | 1782612 |
| 150.0 | 750/0.5 | 355 | - | 1708535 | 2240918 |
| 185.0 | 931/0.5 | 415 | - | 2099430 | 2726261 |
| 240.0 | 1200/0.5 | 500 | - | 2728503 | 3687049 |
| 300.0 | 1500/0.5 | 550 | - | 3403504 | 4605465 |

KĀBEL

# CONTROL CABLES




Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Control Cables (JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

| Rate per 100 meter | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Size (Sq.mm) | CONFIG. | AMPS | 5 CORE * | 6 CORE * | 7 CORE * | 8 CORE * | 10 CORE * | 12 CORE * | 14 CORE * | 16 CORE * | 19 CORE * | 24 CORE * |
| 0.5 | 16/0.2 | 5 | 12461 | 14541 | 16372 | 19246 | 23870 | 28036 | 32804 | 36436 | 44280 | 55027 |
| 0.75 | 24/0.2 | 8 | 17002 | 20448 | 23144 | 27483 | 33936 | 40363 | 46876 | 52946 | 65769 | 80757 |
| 1.0 | 32/0.2 | 13 | 21709 | 25699 | 29847 | 35555 | 44310 | 52074 | 60995 | 68387 | 84315 | 103769 |
| 1.5 | 30/0.25 | 17 | 30668 | 37132 | 42481 | 49821 | 62377 | 73625 | 85725 | 97497 | 115360 | 147808 |
| 2.5 | 50/0.25 | 24 | 48874 | 59258 | 69254 | 80307 | 101186 | 119158 | 137033 | 159778 | 191884 | 240879 |
| 4.0 | 56/0.3 | 30 | 75906 | 92407 | 106760 | 128245 | 160284 | 189866 | 221132 | 252025 | 297728 | 380396 |
| 6.0 | 84/0.3 | 38 | 113109 | 136882 | 159523 | 184546 | 235807 | 279519 | 324003 | 369036 | 435470 | 555626 |
| 10.0 | 140/0.3 | 52 | 193259 | - | - | - | - | - | - | - | - | - |
| 16.0 | 126/0.4 | 70 | 304528 | - | - | - | - | - | - | - | - | - |

Loading factor for Different Insulation / Sheath * -

| Sizes 0.50 to 16.0 Sq.mm | | | All sizes | | |
|---|---|---|---|---|---|
| FR Insulation | FR Sheath | FR-LSH / HR Insulation | FR-LSH / HR Sheath | LSOH Insulation | LSZH Sheath |
| 5% | 5% | 10% | 10% | 35% | 25% |

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

RR KĀBEL

## SUBMERSIBLE FLAT CABLES

3 Core PVC Insulated and sheathed Industrial Flat cables for Submersible Motor, working voltages upto and including 1100 Volts, as per IS 694




| Size (Sq.mm) | * Configuration | Rate 100 mtr |
|---|---|---|
| 1.5 | 30/0.25 | 16971 |
| 2.5 | 50/0.25 | 27600 |
| 4.0 | 56/0.3 | 43119 |
| 6.0 | 84/0.3 | 63391 |
| 10.0 | 140/0.3 | 109191 |
| 16.0 | 126/0.4 | 171975 |
| 25.0 | 196/0.4 | 267247 |

For XLPE Insulated Submersible Flat Cables (Cu/XLPE/PVC), contact us for pricing and availability. MOQ will be applicable.
* As per IS 8130



# SUBMERSIBLE FLAT CABLES FOR THE HARSHEST CONDITIONS

REACH
RoHS • CE
COMPLIANT

SUPERIOR FLEXIBILITY • RUGGED FLAT CONSTRUCTION

WATER & ABRASION RESISTANT • ADVANCE XLPE INSULATION OPTIONS

FLAME RETARDANT

KĀBEL

# SHIELDED CABLES




Flexible / Stranded Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | |
|---|---|---|---|---|---|---|
| SIZE | 0.50 | 0 75 | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 2 Core | 10537 | 12780 | 14888 | 19037 | 28000 | 3 |
| 3 Core | 13188 | 16532 | 19644 | 25357 | 38917 | 3 |
| 4 Core | 16494 | 20931 | 25137 | 33180 | 50191 | 3 |
| 5 Core | 18953 | 24581 | 29856 | 39992 | 62335 | 3 |
| 6 Core | 22147 | 28864 | 35528 | 46613 | - | 3 |
| 7 Core | 24573 | 32415 | 39690 | 53055 | 81671 | 3 |
| 8 Core | 27850 | 36905 | 44934 | 60788 | 96948 | 2 |
| 9 Core | 30793 | - | - | - | - | 2 |
| 10 Core | 34145 | 45399 | 55924 | 76723 | 120229 | 2 |
| 12 Core | 39555 | 53085 | 66313 | 89627 | 142542 | 2 |
| 14 Core | 45038 | 60230 | 76321 | 103600 | 167058 | 1 |
| 16 Core | 51081 | 69958 | 86257 | 117445 | 190668 | 1 |
| 18 Core | 56722 | 77179 | 96279 | 131262 | 215149 | 1 |
| 20 Core | 62725 | 84629 | 106799 | 150326 | 238681 | 1 |
| 22 Core | 69067 | 93416 | 116877 | - | - | 1 |
| 25 Core | 77470 | 105145 | 133040 | - | - | 1 |
| 27 Core | 83011 | 112866 | 141607 | - | - | 1 |

Note : Please contact to HO for Techni

# SHIELDED ARMOURED CABLES




Flexible / Stranded Bare Copper Conductor PVC / XLPE Insulated,
Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour And Outer PVC Sheathed Industrial Instrumentation (Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | |
|---|---|---|---|---|---|---|
| SIZE | 0 50 | 0.75 | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 2 Core | 16623 | 19861 | 23235 | 29348 | 41058 | 5 |
| 3 Core | 19943 | 24624 | 29486 | 38367 | 55225 | 5 |
| 4 Core | 23535 | 29680 | 36105 | 47736 | 69734 | 3 |
| 5 Core | 27307 | 34942 | 42801 | 57350 | 84428 | 3 |
| 6 Core | 31445 | 40513 | 49997 | 67123 | - | 3 |
| 7 Core | 34411 | 44856 | 55827 | 75563 | 113456 | 3 |
| 8 Core | 38642 | 50664 | 62987 | 85709 | 129697 | 3 |
| 9 Core | 43528 | - | - | - | - | 3 |
| 10 Core | 46196 | 61045 | 76449 | 104026 | 157346 | 3 |
| 12 Core | 52482 | 70370 | 88581 | 121426 | 184851 | 3 |
| 14 Core | 61303 | 82173 | 106739 | 139384 | 212761 | 3 |
| 16 Core | 66403 | 94988 | 112659 | 157392 | 240793 | 3 |
| 18 Core | 73059 | 98378 | 125389 | 175306 | 269107 | 3 |
| 20 Core | 85804 | 108152 | 138255 | 193415 | 297607 | 2 |
| 22 Core | 94545 | 118986 | 152125 | - | - | 2 |
| 24 Core | - | - | 162414 | - | - | 2 |
| 25 Core | 95151 | 135304 | 169219 | - | - | 2 |
| 27 Core | 101367 | 146195 | 182658 | - | - | 2 |

Note : Please contact to HO for Technical Data Sheet.

# BRAIDED CABLES




Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | |
|---|---|---|---|---|---|---|
| **SIZE** | **0.25** | **0.50** | **0.75** | **1.00** | **1.50** | **2.50** |
| 2 Core | 13918 | 16026 | 17397 | 19692 | 25106 | 36753 |
| 3 Core | 14971 | 17878 | 21607 | 24870 | 32456 | 48249 |
| 4 Core | 18001 | 21865 | 26773 | 31489 | 40603 | 61882 |
| 5 Core | 22546 | 25546 | 32053 | 37534 | 49616 | - |
| 6 Core | 26558 | 28203 | 33914 | 42580 | 55714 | - |
| 7 Core | 28033 | 30621 | 39101 | 46992 | 62881 | - |
| 8 Core | 30035 | 34537 | 43773 | 53521 | 72638 | - |
| 9 Core | - | - | - | - | 81262 | - |
| 10 Core | 35891 | 43869 | 55616 | 66272 | 90282 | - |
| 12 Core | 39769 | 47718 | 63795 | 77540 | 105157 | - |
| 14 Core | - | 54667 | 72808 | 89706 | 121995 | - |
| 16 Core | - | 61535 | 82081 | 100970 | 137358 | - |
| 18 Core | 55968 | 67906 | 92002 | 112947 | 145334 | - |

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | |
|---|---|---|---|---|
| **SIZE** | **4.0** | **6.0** | **10.0** | **16.0** |
| 2 Core | 53053 | 73118 | - | - |
| 3 Core | 72837 | 101308 | - | - |
| 4 Core | 91699 | 129197 | 216898 | 350890 |

Note : Please contact HO for Technical Data Sheet.

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,
0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.

# PAIR SHIELDED CABLES




Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|---|---|---|---|---|---|---|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 1 | 12754 | 15620 | 10 | 19355 | 22295 | 32081 | 5 |
| 2 | 20892 | 25390 | 5 | 32393 | 40249 | 60314 | 3 |
| 3 | 27045 | 34135 | 3 | 43037 | 56765 | 85783 | 3 |
| 4 | 31451 | 43901 | 3 | 55250 | 72208 | 112061 | 3 |
| 5 | 38332 | 53522 | 3 | 68495 | 87514 | 134041 | 3 |
| 6 | 44729 | 62868 | 3 | 81558 | 103702 | 159353 | 2 |
| 8 | 57419 | 80835 | 3 | 102453 | 137155 | 209793 | 2 |
| 10 | 70673 | 98203 | 3 | 126097 | 167887 | 260066 | 2 |
| 12 | 84099 | 117355 | 3 | 149684 | 199820 | 310246 | 2 |
| 14 | - | - | - | - | 229210 | - | 1 |
| 16 | 109227 | 153458 | 2 | 198308 | 265807 | 414012 | 1 |
| 20 | 135645 | 191318 | 2 | 245497 | 329889 | 514765 | 1 |
| 24 | 160920 | 227613 | 2 | 292560 | 393786 | 615376 | 1 |

Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|---|---|---|---|---|---|---|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 2 | 27112 | 31563 | 5 | 38666 | 47917 | 68348 | 2 |
| 3 | 35206 | 43794 | 5 | 54291 | 66961 | 96846 | 2 |
| 4 | 44958 | 54853 | 3 | 65958 | 87169 | 126762 | 2 |
| 5 | 53101 | 66540 | 3 | 82708 | 105804 | 154694 | 1 |
| 6 | 63098 | 80085 | 2 | 96970 | 125600 | 184086 | 1 |
| 8 | 84359 | 104496 | 2 | 128152 | 165073 | 242808 | 1 |
| 10 | 103666 | 128828 | 1 | 158290 | 204410 | 301364 | 1 |
| 12 | 122939 | 153085 | 1 | 188402 | 236761 | 359817 | 1 |
| 16 | 162306 | 197362 | 1 | 241147 | 315349 | 466780 | 1 |
| 20 | 200921 | 244711 | 1 | 302225 | 392061 | 581061 | 1 |
| 24 | 239503 | 292068 | 1 | 360979 | 468731 | 695300 | 1 |
| 25 | - | - | - | 375672 | - | - | 1 |

Note: The MOQ is given above, please contact HO for Technical Data Sheet.

# PAIR SHIELDED ARMOURED CABLES




Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire/Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Overall Pair Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|---|---|---|---|---|---|---|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 1 | 16487 | 19829 | 10 | 23163 | 29415 | 41382 | 5 |
| 2 | 25983 | 32507 | 5 | 38985 | 51110 | 73916 | 3 |
| 3 | 32093 | 41412 | 3 | 50765 | 68750 | 106830 | 3 |
| 4 | 39582 | 51760 | 3 | 64151 | 87430 | 129549 | 3 |
| 5 | 46941 | 61991 | 3 | 77419 | 105176 | 158892 | 3 |
| 6 | 54092 | 72034 | 3 | 95933 | 123828 | 188170 | 2 |
| 8 | 73398 | 91366 | 3 | 115686 | 160931 | 246253 | 2 |
| 10 | 81177 | 111007 | 3 | 141399 | 197564 | 302249 | 2 |
| 12 | 95312 | 130565 | 3 | 167114 | 234132 | 359918 | 2 |
| 14 | - | - | - | - | 273282 | - | 1 |
| 16 | 123307 | 169829 | 2 | 217768 | 306623 | 474290 | 1 |
| 20 | 152347 | 211342 | 2 | 272320 | 384235 | 598208 | 1 |
| 24 | 182925 | 253727 | 2 | 326888 | 461261 | 718047 | 1 |

Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual Pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Individual Pair and Overall Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|---|---|---|---|---|---|---|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 2 | 32740 | 39258 | 5 | 45734 | 58052 | 86543 | 2 |
| 3 | 42440 | 51694 | 5 | 61014 | 79072 | 112263 | 2 |
| 4 | 53338 | 65685 | 3 | 77919 | 107232 | 143869 | 2 |
| 5 | 64146 | 79194 | 3 | 100595 | 122813 | 176586 | 1 |
| 6 | 74714 | 93467 | 2 | 110872 | 144905 | 209029 | 1 |
| 8 | 96510 | 119497 | 2 | 143780 | 189607 | 274296 | 1 |
| 10 | 117244 | 147590 | 1 | 178241 | 234964 | 341646 | 1 |
| 12 | 138674 | 174391 | 1 | 210737 | 279045 | 406824 | 1 |
| 16 | 180464 | 227271 | 1 | 276456 | 366843 | 537113 | 1 |
| 20 | 223549 | 283014 | 1 | 344542 | 458004 | 672391 | 1 |
| 24 | 268371 | 339742 | 1 | 413579 | 549705 | 806975 | 1 |
| 25 | - | - | - | 429134 | - | - | 1 |

Note: The MOQ is given above, please contact HO for Technical Data Sheet.

RR KĀBEL

## Solar DC Cables




ATC Conductor, Single Core UV resistant, E-Beam Crosslinked, Halogen Free Flame Retardant insulated and sheathed cable as per IS 17293, EN 50618 and IEC 62930, suitable for 1/1 (1.2) KV AC; 1.5/1.5 (1.8) KV DC Unearthed System.

| Size (Sq.mm) | * Configuration | Rate / 100 Mtr | Coils packed in a Outer Box |
|---|---|---|---|
| 2.5 | 50 / 0.25 | 10431 | 100 / 200 Mtr |
| 4.0 | 56 / 0.3 | 14866 | 500 / 1000 / 2000 Mtr |
| 6.0 | 84 / 0.3 | 21862 | 500 / 1000 / 2000 Mtr |
| 10.0 | 140 / 0.3 | 38935 | 500 / 1000 Mtr |
| 16.0 | 126 / 0.4 | 60557 | 500 / 1000 Mtr |

* As per IS 8130

# SOLAR CABLES THAT DON'T JUST TRANSMIT POWER EFFICIENTLY, THEY EMPOWER A BRIGHTER FUTURE.

- UV RESISTANT
- EXTREME TEMPERATURE RESISTANT
- OZONE RESISTANT
- CE, REACH & ROHS COMPLIANT

# AKALMAND BANO, SAHI CHUNO.

## TERMS & CONDITIONS:

| | | |
|---|---|---|
| GST | : | The above prices are exclusive of GST. |
| Packing | : | Order should be in Standard packing. |
| Freight | : | Consignment value upto Rs.200000/- on topay basis and above on "Paid" basis. |
| Note | : | This is Revised Price List, hence all previous Price List & Discount will not be considered. |

**As per the international practice which is also adopted by BIS, for all cables with ISI mark the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, it may vary within the prescribed limit of IS:8130, with related classes and tables.

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

Ref No. RRKL/LP/LDC-PIIC/11-2/26 w.e.f. 17th November 2026

RR GLOBAL

# WORLD OF EXCELLENCE



As a USD 1.6+ billion conglomerate, we are one of the largest, diversified & most prominent brands in the Indian electrical industry, with a noteworthy presence in over 90+ countries across the world. We offer a multi faceted range of quality products through our 10 successfully operating companies, 45 marketing offices and 23 manufacturing facilities.
At RR Global, we continue to innovate to ensure only the finest products reach our customers.



Ram Ratna House, Utopia City, P. B. Marg, Worli, Mumbai - 400 013.
**T:** +91 - 22 - 2494 9009 / 2492 4144 • **F:** +91 - 22 - 2491 2586 • **E:** mumbai.rrkabel@rrglobal.com

Alembic Business Park (W), Ground Floor, Bhailal Amin Marg, Gorwa, Vadodara - 390 003
**T** : +91-265-6830 800 • **E:** vadodara.rrkabel@rrglobal.com

---

## R R KABEL LIMITED

**Regd. Office :** Ram Ratna House, Utopia City, P. B. Marg, Worli, Mumbai - 400 013.

**Ahmedabad:** 079 - 4900 0100, **Bengaluru:** 080 - 4125 0079 / 4090 2221, **Bhubaneswar:** 08596 970 402, **Chennai:** 044 - 2829 2329 / 2429, **Coimbatore:** 09025 168 457, **Ernakulam:** 0484 - 2378 783, **Gurugram:** 0124 - 6549 100, **Guwahati:** 09365 287 997, **Indore:** 0731 - 3515 577, **Jaipur:** 0141 - 2741417, **Kolkata:** 033 - 6607 1233, **Lucknow:** 0522 - 3516 188/89, **Madurai:** 0452 - 2913 639, **Pune:** 07486 989 082, **Raipur:** 0771 - 4051 518, **Secunderabad:** 040 - 2780 4098, **Silvassa:** 0260 - 2641 332/33, **Sonipat:** 0130 - 2986 986, **Surat:** 09376 507 543, **Trichy:** 0431 - 2903 906, **Vijaywada:** 09966 999 626, **Zirakpur:** 07486 870 737.

**www.rrkabel.com • www.rrglobal.com**

---

**REACH** = Registration, Evaluation, Authorisation and Restriction of Chemicals
**RoHS** = Restriction of Hazardous Substances | **CE** = Conformite Europeenne
**ISI** = Indian Standard Institution